

HDP624-XXXYYYT

30 Watt Switch Mode Wall Power Supply

with interchangeable input adapters



Features

- High reliability
- Built-in OVP, OCP, and SCP
- 100% smart burn-in test for 4 hours

Dimensions

76.8 x 48 x 31 mm

Weight

~120g

Electrical Specifications

INPUT RANGE	100 - 240 VAC (Full Range), 50/60 Hz
INPUT CURRENT (RMS)	0.8A@90VAC; 0.4A@264VAC max
VOLTAGE RANGE	DC 5 - 30V output
VOLTAGE REGULATION	±5% @ constant voltage mode
CURRENT RANGE	0.01 - 4.0A
MAX OUTPUT POWER	30W Max
PROTECTION	Over Current, Over Voltage, Short Circuit Protection
EFFICIENCY	Meets CEC VI

Environmental & Reliability

OPERATING TEMPERATURE	0°C ~ +45°C ambient
STORAGE TEMPERATURE	-20°C ~ +80°C
MTBF	>25k Hours at 80% load and 25°C ambient temperature

Safety, Efficiency, & EMC Standards

CB, UL, ETL, FCC, ICES, GS, CE, LVD, SAA, C-Tick/RCM, CCC, PSE, RoHS, REACH, PAHS

